CHECKLIST TOLDOOL BAIS			
Which door shall be secured?	PR1400	PR1500	PR2600
Main entrance, apartment, basement, side entrance door: lockable from both in- and outside!	_	_	
As described, plus partial opening of the door possible!			
Basement and side entrance door: lockable only from the inside!	_	_	_
			_
How wide is the door panel (on the inside)?	PR1400	PR1500	PR2600
mm			
Note: In case there is not enough space next to the panel	850 - 1000 mm	780 - 1040 mm	735 - 1030 mm
to mount the lock cases, wall anchored strikes can be fitted. One strike is included in the packaging.		1040 - 1440 mm with extension barrel	
How thick is the door?	PR1400	PR1500	PR2600
mm		_	
	suitable for all door		35 - 50 mm 30/60
	thicknesses		
			51 - 60 mm 30/70
			61 - 70 mm 30/80
			71 - 80 mm 30/90
How does the door open?	PR1400	PR1500	PR2600
to the inside			
to the outside		_	
	PA1018		PA1018
** PA 1018 and if necessary spacer for lock body			
Shall the exterior cylinder be protected additionally against brutal attacks?	PR2600		
yes Cylinder length for PZS 1000: 0-9,5 mm protruding from the door	_		
no			
	_		

